00888158
COMPOSITE REVERSE OSMOSIS MEMBRANE AND METHOD OF REVERSE OSMOTIC TREATMENT OF
    WATER USING THE SAME
VERBUNDMEMBRAN   FUR   UMKEHROSMOSE   UND   METHODE   ZUR   WASSERBEHANDLUNG   MIT
    UMKEHROSMOSE MIT HILFE DERSELBEN
MEMBRANE D'OSMOSE INVERSE COMPOSITE, ET PROCEDE DE TRAITEMENT DE L'EAU PAR
    OSMOSE INVERSE A L'AIDE DE LADITE MEMBRANE
PATENT ASSIGNEE:
  NITTO DENKO CORPORATION, (301875), 1-2, Shimohozumi 1-chome Ibaraki-shi,
    Osaka 567, (JP), (applicant designated states: DE;FR;GB;IT)
INVENTOR:
  HACHISUKA, Hisao, Room No. 501, Ranburasu Saga, 9-1,
    Setogawacho,Sagatenryuji, Ukyo-ku,, Kyoto-shi, Kyoto 616, (JP)
  IKEDA, Kenichi, 218-21, Aojicho, Kusatsu-shi, Shiga 525, (JP)
LEGAL REPRESENTATIVE:
  Schwarzensteiner, Marie-Luise et al (78601), Grape & Schwarzensteiner
    Patentanwalte Sebastiansplatz 7, 80331 Munchen, (DE)
PATENT (CC, No, Kind, Date): EP 888810 A1 990107 (Basic)
                              WO 9734686 970925
APPLICATION (CC, No, Date):   EP 97907348 970317; WO 97JP856 970317
PRIORITY (CC, No, Date): JP 9661477 960318; JP 96102657 960424; JP 96112542
    960507
DESIGNATED STATES: DE; FR; GB; IT
INTERNATIONAL PATENT CLASS: B01D-069/02; B01D-069/12; B01D-071/56; B01D-061/02;

ABSTRACT WORD COUNT: 117

LANGUAGE (Publication,Procedural,Application): English; English; Japanese
FULLTEXT AVAILABILITY:

Available Text	Language	Update	Word Count
CLAIMS A	(English)	9901	527
SPEC A	(English)	9901	4968
Total word count - document A			5495
Total word count - document B			0
Total word count - documents A + B			5495

...SPECIFICATION acetate. On the other hand, reverse osmosis composite
  membranes, in which an active thin film substantially having a selective
  separation property is formed on a **microporous** support film, are known as
  reverse osmosis membranes having a different structure from the asymmetric
  reverse osmosis membranes.
    Presently, a number of such reverse osmosis...
...amine and polyfunctional alicyclic acid halide has a negative charge due to
  the residual carboxylic acid. The membrane surface having negative charge
  adsorbs, for example, cationic fouling substances, **decreasing** the **flux**.
  Therefore, a **membrane** has been required that is neutral in charge and has a
  high water permeability and a high salt rejection.

Disclosure of Invention
    It is an...were added to an aqueous solution containing 3.0 wt.% of
  m-phenylenediamine and 0.15 wt.% of sodium lauryl sulfate was contacted with
  a **microporous** polysulfone support film for several seconds, and the excess
  solution was removed to form a layer of the solution on the support film.
    Next, the...were added to an aqueous solution containing 3.0 wt.% of

m-phenylenediamine and 0.15 wt.% of sodium lauryl sulfate was contacted with a **microporous** polysulfone support film for several seconds, and the excess solution was removed to form a layer of the solution on the support film.
Next, the...

...was set in a flat membrane cell, and water obtained by filtering general domestic waste water containing 1 ppm of a surfactant with a water **MF** filter was pressure circulated at a pressure of 15 kgf/ ...were added to an aqueous solution containing 2.0 wt.% of m-phenylenediamine and 0.15 wt.% of sodium lauryl sulfate was contacted with a **microporous** polysulfone support film for several seconds, and the excess solution was removed to form a layer of the solution on the support film.
Next, the...